

SL-88-OEM

OEM Compact Backlit Industrial Keyboard

The SL-88-OEM by iKey®, when properly installed, is designed to meet NEMA 4X specifications and is ideal for industrial, kiosk and mobile computing applications. It is a compact keyboard featuring red LED backlit keys and an industrial silicone rubber keypad. The SL-88-OEM has a secondary legend accessed with the NumLock and Fn key.

Features:

- 12 Function Keys
- 88-Key Functionality
- Integrated Backlighting
- USB and PS/2 configurations available
- Optional NVIS Compliant – Green B backlighting



Product Code SL-88-OEM

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10' straight (3 m)
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from USB port)
FLAMMABILITY	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40F to +194F (-40C to +90C) OPERATING: -40F to 158F (-40C to +70C)
WEIGHT	1.00 lbs +/-0.10 lbs (0.45 kg +/- 0.05 kg)
WARRANTY	90 day limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	11.12" x 6.05" x 0.38" (l-h-d) 282.4mm x 153.7mm x 8.6mm
MODEL NUMBERS	SL-88-OEM-PS2: With PS/2 cable SL-88-OEM-USB: With USB cable